

Black Industrial Finish - Rust Resistant • MOC : Chrome Vanadium Steel

RING TYPE STRAIGHT SLUGGING WRENCHES

(Conforming to DIN 7444)

Metric Size Part No.	A/F Size (mm)	American Size Part No.	A/F Size (inch)	Approx. Head Depth	Approx. Head Dia.	Approx. OAL (mm)
GSW-24	24	GSW-15/16	15/16"	15	43	165
GSW-25	25	GSW-1	1"	15	43	165
GSW-27	27	GSW-1.1/16	1.1/16"	16	46	180
GSW-29	29	GSW-1.1/8	1.1/8"	16	46	180
GSW-30	30	GSW-1.3/16	1.3/16"	17	52	190
GSW-32	32	GSW-1.1/4	1.1/4"	17	52	190
GSW-33	33	GSW-1.5/16	1.5/16"	17	52	190
GSW-35	35	GSW-1.3/8	1.3/8"	18	58	205
GSW-36	36	GSW-1.7/16	1.7/16"	18	58	205
GSW-38	38	GSW-1.1/2	1.1/2"	18	58	205
GSW-41	41	GSW-1.5/8	1.5/8"	20	66	230
GSW-43	43	GSW-1.11/16	1.11/16"	20	66	230
GSW-44	44	GSW-1.3/4	1.3/4"	22	74	240
GSW-46	46	GSW-1.13/16	1.13/16"	22	74	240
GSW-47	47	GSW-1.7/8	1.7/8"	22	74	240
GSW-50	50	GSW-2	2"	24	80	255
GSW-52	52	GSW-2.1/16	2.1/16"	24	80	255
GSW-55	55	GSW-2.3/16	2.3/16"	25	86	270
GSW-57	57	GSW-2.1/4	2.1/4"	25	86	270
GSW-60	60	GSW-2.3/8	2.3/8"	26	93	280
GSW-62	62	GSW-2.7/16	2.7/16"	26	93	280
GSW-63	63	GSW-2.1/2	2.1/2"	26	93	280
GSW-65	65	GSW-2.9/16	2.9/16"	30	102	300
GSW-67	67	GSW-2.5/8	2.5/8"	30	102	300
GSW-70	70	GSW-2.3/4	2.3/4"	33	110	330
GSW-71	71	GSW-2.13/16	2.13/16"	33	110	330
GSW-75	75	GSW-2.15/16	2.15/16"	33	110	330
GSW-76	76	GSW-3	3"	33	110	330
GSW-80	80	GSW-3.1/8	3.1/8"	36	126	360
GSW-85	85	GSW-3.1/4	3.1/4"	36	126	360
GSW-90	90	GSW-3.5/8	3.5/8"	40	142	390
GSW-95	95	GSW-3.3/4	3.3/4"	40	142	390
GSW-97	97	GSW-3.7/8	3.7/8"	45	155	420
GSW-100	100	GSW-4	4"	45	155	420
GSW-105	105	GSW-4.1/8	4.1/8"	45	155	420
GSW-110	110	GSW-4.1/4	4.1/4"	48	170	450
GSW-115	115	GSW-4.1/2	4.1/2"	48	170	450
GSW-120	120	GSW-4.3/4	4.3/4"	54	182	480
GSW-125	125	GSW-4.7/8	4.7/8"	54	182	480
-	-	GSW-5	5"	54	182	480
GSW-130	130	GSW-5.1/8	5.1/8"	58	202	520
GSW-135	135	GSW-5.1/4	5.1/4"	58	202	520
GSW-140	140	GSW-5.1/2	5.1/2"	58	210	520

OPEN TYPE STRAIGHT SLUGGING WRENCHES

(Conforming to DIN 133)

Metric Size Part No.	A/F Size (mm)	American Size Part No.	A/F Size (inch)	Approx. Head Depth	Approx. Head Dia.	Approx. OAL (mm)
GSWO-24	24	GSWO-15/16	15/16"	16	56	180
GSWO-25	25	GSWO-1	1"	16	56	180
GSWO-27	27	GSWO-1.1/16	1.1/16"	16	56	180
GSWO-29	29	GSWO-1.1/8	1.1/8"	16	56	180
GSWO-30	30	GSWO-1.3/16	1.3/16"	17	62	190
GSWO-32	32	GSWO-1.1/4	1.1/4"	17	62	190
GSWO-33	33	GSWO-1.5/16	1.5/16"	17	62	190
GSWO-35	35	GSWO-1.3/8	1.3/8"	17.5	76	215
GSWO-36	36	GSWO-1.7/16	1.7/16"	17.5	76	215
GSWO-38	38	GSWO-1.1/2	1.1/2"	17.5	76	215
GSWO-41	41	GSWO-1.5/8	1.5/8"	18.5	86	235
GSWO-43	43	GSWO-1.11/16	1.11/16"	18.5	86	235
GSWO-44	44	GSWO-1.3/4	1.3/4"	18.5	86	235
GSWO-46	46	GSWO-1.13/16	1.13/16"	20	98	255
GSWO-47	47	GSWO-1.7/8	1.7/8"	20	98	255
GSWO-50	50	GSWO-2	2"	21	105	275
GSWO-52	52	GSWO-2.1/16	2.1/16"	21	105	275
GSWO-55	55	GSWO-2.3/16	2.3/16"	23	116	300
GSWO-57	57	GSWO-2.1/4	2.1/4"	23	116	300
GSWO-60	60	GSWO-2.3/8	2.3/8"	24.5	128	320
GSWO-62	62	GSWO-2.7/16	2.7/16"	24.5	128	320
GSWO-63	63	GSWO-2.1/2	2.1/2"	24.5	128	320
GSWO-65	65	GSWO-2.9/16	2.9/16"	27	138	342
GSWO-67	67	GSWO-2.5/8	2.5/8"	27	138	342
GSWO-70	70	GSWO-2.3/4	2.3/4"	30	154	375
GSWO-71	71	GSWO-2.13/16	2.13/16"	30	154	375
GSWO-75	75	GSWO-2.15/16	2.15/16"	30	154	375
GSWO-76	76	GSWO-3	3"	30	154	375
GSWO-80	80	GSWO-3.1/8	3.1/8"	34	174	408
GSWO-85	85	GSWO-3.1/4	3.1/4"	34	174	408
GSWO-90	90	GSWO-3.5/8	3.5/8"	38	194	445
GSWO-95	95	GSWO-3.3/4	3.3/4"	38	194	445
GSWO-97	97	GSWO-3.7/8	3.7/8"	44	215	485
GSWO-100	100	GSWO-4	4"	44	215	485
GSWO-105	105	GSWO-4.1/8	4.1/8"	44	215	485
GSWO-110	110	GSWO-4.1/4	4.1/4"	47	235	510
GSWO-115	115	GSWO-4.1/2	4.1/2"	47	235	510
GSWO-120	120	GSWO-4.3/4	4.3/4"	50	255	545
GSWO-125	125	GSWO-4.7/8	4.7/8"	50	255	545
-	-	GSWO-5	5"	50	255	545
GSWO-130	130	GSWO-5.1/8	5.1/8"	50	255	545
GSWO-135	135	GSWO-5.1/4	5.1/4"	55	275	575
GSWO-140	140	GSWO-5.1/2	5.1/2"	55	275	575

AVAILABLE AS PER IS 4509:1992 ON REQUEST

AVAILABLE AS PER IS 4508:1992 ON REQUEST

SPECIAL SIZES ARE AVAILABLE AGAINST SPECIFIC ORDERS



RING TYPE STRAIGHT SLUGGING WRENCHES



OPEN TYPE STRAIGHT SLUGGING WRENCHES

HEAVY DUTY INSERT SOCKETS

Metric Size Part No.	A/F Size (mm)	American Size Part No.	A/F Size (inch)	Outside Dia.	Apprx. OAL	Bolt Clear. Dia.	Hex Position Length
GINS-24	24	GINS-15/16	15/16"	44.0	65	18	22
-	-	GINS-1	1"	44.0	65	18	22
GINS-27	27	GINS-1.1/16	1.1/16"	48.0	65	20	22
-	-	GINS-1.1/8	1.1/8"	48.0	65	20	22
-	-	GINS-1.3/16	1.3/16"	52.0	65	22	22
GINS-30	30	GINS-1.1/4	1.1/4"	54.0	65	23	22
GINS-32	32	GINS-1.5/16	1.5/16"	54.0	75	24	27
GINS-34	34	GINS-1.3/8	1.3/8"	57.5	75	25	27
GINS-36	36	GINS-1.7/16	1.7/16"	59.0	75	26	27
GINS-38	38	GINS-1.1/2	1.1/2"	59.0	75	28	27
-	-	GINS-1.9/16	1.9/16"	63.5	75	29	27
GINS-41	41	GINS-1.5/8	1.5/8"	67.0	85	29	30
GINS-42	42	GINS-1.11/16	1.11/16"	68.0	85	31	32
GINS-46	46	GINS-1.3/4	1.3/4"	72.0	88	32	33
-	-	GINS-1.13/16	1.13/16"	72.0	88	32	33
-	-	GINS-1.7/8	1.7/8"	74.0	88	34	33
GINS-50	50	GINS-2	2"	78.0	94	37	36
-	-	GINS-2.1/16	2.1/16"	79.0	94	37	36
-	-	GINS-2.1/8	2.1/8"	86.0	96	37	37
GINS-55	55	GINS-2.3/16	2.3/16"	86.0	96	38	37
-	-	GINS-2.1/4	2.1/4"	88.0	96	40	37
-	-	GINS-2.5/16	2.5/16"	89.0	108	41	43
GINS-60	60	GINS-2.3/8	2.3/8"	89.0	108	43	43
-	-	GINS-2.1/2	2.1/2"	95.0	112	43	46
GINS-65	65	GINS-2.9/16	2.9/16"	98.0	112	44	46
-	-	GINS-2.5/8	2.5/8"	98.0	112	46.5	46
-	-	GINS-2.11/16	2.11/16"	99.0	120	46.5	49
GINS-70	70	GINS-2.3/4	2.3/4"	108.0	120	47.5	49
-	-	GINS-2.13/16	2.13/16"	108.0	120	50	49
GINS-75	75	GINS-2.15/16	2.15/16"	109.0	127	52	52
-	-	GINS-3	3"	109.0	127	53	52
-	-	GINS-3.1/8	3.1/8"	115.0	135	55	56
GINS-80	80	GINS-3.3/16	3.3/16"	118.0	135	55	56
-	-	GINS-3.1/4	3.1/4"	118.0	140	58	56
-	-	GINS-3.5/16	3.5/16"	118.0	140	60	56
GINS-85	85	GINS-3.3/8	3.3/8"	128.0	140	60	56
GINS-90	90	GINS-3.1/2	3.1/2"	128.0	145	65	56
GINS-95	95	GINS-3.3/4	3.3/4"	138.0	150	70	62
GINS-100	100	GINS-3.7/8	3.7/8"	138.0	155	75	62
GINS-105	105	GINS-4	4"	148.0	155	75	62
GINS-110	110	GINS-4.1/8	4.1/8"	148.0	180	80	72
GINS-115	115	GINS-4.3/8	4.3/8"	158.0	190	82	77
GINS-120	120	GINS-4.1/2	4.1/2"	169.0	190	86	77
GINS-125	125	GINS-4.3/4	4.3/4"	176.0	190	90	82
GINS-130	130	GINS-4.7/8	4.7/8"	178.0	205	90	82
GINS-135	135	GINS-5.5/16	5.5/16"	186.0	210	100	82
GINS-140	140	GINS-5.1/2	5.1/2"	188.0	210	105	82

