

SINGLE ACTING HYDRAULIC CYLINDERS

- ◆ Collar threads, plunger threads and base mounting holes in many models for the suitability of most applications.
- ◆ Designed for use in all positions.
- ◆ High strength alloy steel for durability.
- ◆ Heavy duty return springs.
- ◆ Corrosion resistant special painting.
- ◆ Plunger wiper reduces dust particles contamination for extending cylinder life.



Part No.	Capacity (ton)	Stroke (mm)	Oil Capacity (cm ³)	Collapsed Height (mm)	Weight (kg)
GRC-50	5	16	10	41	1.0
GRC-51		25	16	110	1.0
GRC-53		76	50	165	1.5
GRC-55		127	83	215	1.9
GRC-57		177	115	273	2.4
GRC-59		232	151	323	2.8
GRC-101		10	26	38	89
GRC-102	54		78	121	2.3
GRC-104	105		152	171	3.3
GRC-106	156		226	247	4.4
GRC-108	203		294	298	5.4
GRC-1010	257		373	349	6.4
GRC-1012	304		441	400	6.8
GRC-1014	356		516	450	8.2
GRC-151	15	25	51	124	3.3
GRC-152		51	104	149	4.1
GRC-154		101	205	200	5.0
GRC-156		152	308	271	6.8
GRC-158		203	411	322	8.2
GRC-1510		254	516	373	9.5
GRC-1512		305	619	423	10.9
GRC-1514		356	723	474	11.8
GRC-251	25	26	86	139	5.9
GRC-252		50	166	165	6.4
GRC-254		102	339	215	8.2
GRC-256		158	525	273	10.0
GRC-258		210	697	323	12.2
GRC-2510		261	867	374	14.1
GRC-2512		311	1033	425	16.3
GRC-2514		362	1202	476	17.7
GRC-308	30	209	880	387	18.1
GRC-502	50	51	362	176	15.0
GRC-504		101	719	227	19.1
GRC-506		159	1131	282	23.1
GRC-5013		337	2399	460	37.6
GRC-756	75	156	1601	285	29.5
GRC-7513		333	3417	492	59.0
GRC-1006	100	168	2239	357	59.0
GRC-10010		260	3466	449	72.6