

HIGH TONNAGE SINGLE-ACTING HYDRAULIC CYLINDERS - LOAD RETURN

- ◆ Integral stop ring provides piston blow-out protection.
- ◆ Baked enamel outside finish and plated pistons provide superior corrosion protection.
- ◆ Interchangeable, hardened grooved saddles are standard.
- ◆ Base mounting holes are standard on all models.



Part No.	Capacity (ton)	Stroke (mm)	Oil Capacity (cm ³)	Collapsed Height (mm)	Weight (kg)
GLSG-502	50	50	385	162	17
GLSG-504		100	770	212	20
GLSG-506		150	1155	262	23
GLSG-508		200	1540	312	27
GLSG-5010		250	1924	362	31
GLSG-5012		300	2309	412	34
GLSG-1002	100	50	664	182	19
GLSG-1004		100	1327	232	29
GLSG-1006		150	1991	282	40
GLSG-1008		200	2655	332	50
GLSG-10010		250	3318	382	61
GLSG-10012		300	3982	432	71
GLSG-1502	150	50	993	196	39
GLSG-1504		100	1986	246	52
GLSG-1506		150	2978	296	65
GLSG-1508		200	3971	346	78
GLSG-15010		250	4964	396	92
GLSG-15012		300	5957	446	105
GLSG-2002	200	50	1330	216	55
GLSG-2006		150	3989	316	91
GLSG-20012		300	7977	466	146
GLSG-2502	250	50	1832	235	89
GLSG-2506		150	5497	335	136
GLSG-25012		300	10993	485	207
GLSG-3002	300	50	2281	312	184
GLSG-3006		150	6843	412	232
GLSG-30012		300	13685	562	303
GLSG-4002	400	50	2800	375	270
GLSG-4006		150	8399	475	330
GLSG-40012		300	16797	625	421
GLSG-5002	500	50	3653	419	401
GLSG-5006		150	10959	519	480
GLSG-50012		300	21918	669	599
GLSG-6002	600	50	4276	429	474
GLSG-6006		150	12829	529	565
GLSG-60012		300	25659	679	701
GLSG-8002	800	50	5881	474	741
GLSG-8006		150	17644	574	868
GLSG-80012		300	35288	724	1058
GLSG-10002	1000	50	7329	564	1062
GLSG-10006		150	21986	664	1213
GLSG-100012		300	43972	814	1439