

DIAL TYPE TORQUE WRENCHES



- ◆ Non-length dependent design.
- ◆ Alloy steel precision torsion drive.
- ◆ Dual scale.
- ◆ Dual direction.
- ◆ Memory follower needle on each wrench.
- ◆ Dial protected with steel guard.
- ◆ Ranges from 0 in.lb. to 2000 ft.lb.
- ◆ **GRIPHOLD®** calibration certificate traceable to NPL supplied standard.
- ◆ Serial number hard marked on each wrench.
- ◆ 3% accuracy from 20-100% of range.



Part No.	Range	Graduation	Drive	Length	Case	Weight	Memory Needle
D1-30i	0-31 in.lb. 0-3.5 Nm	0.5 in.lb. 0.1 Nm	1/4"	10.63" 270mm	Plastic Blow Molded	1.6lb 0.73kg	YES
D1-75i	0-75 in.lb. 0-9 Nm	1 in.lb. 0.2 Nm	1/4"	10.63" 270mm	Plastic Blow Molded	1.6lb 0.73kg	YES
D1-150i	0-150 in.lb. 0-13 Nm	2 in.lb. 0.5 Nm	3/8"	10.63" 270mm	Plastic Blow Molded	1.6lb 0.73kg	YES
D1-250i	0-250 in.lb. 0-30 Nm	5 in.lb. 0.5 Nm	3/8"	10.63" 270mm	Plastic Blow Molded	1.6lb 0.73kg	YES
D1-600i	0-600 in.lb. 0-70 Nm	10 in.lb. 2 Nm	3/8"	10.63" 270mm	Plastic Blow Molded	1.6lb 0.73kg	YES
D1-50F	0-50 ft.lb. 0-70 Nm	1 ft.lb. 2 Nm	3/8"	10.63" 270mm	Plastic Blow Molded	1.6lb 0.73kg	YES
D3-100F	0-100 ft.lb. 0-140 Nm	2 ft.lb. 2.5 Nm	1/2"	22" 560mm	Plastic Blow Molded	3.0 lb 1.4 Kg	YES
D3-175F	0-175 ft.lb. 0-240 Nm	5 ft.lb. 5 Nm	1/2"	22" 560mm	Plastic Blow Molded	3.0 lb 1.4 Kg	YES
D3-250F	0-250 ft.lb. 0-350 Nm	5 ft.lb. 10 Nm	1/2"	22" 560mm	Plastic Blow Molded	3.0 lb 1.4 Kg	YES
D4-350F(M)*	0-350 ft.lb. 0-480 Nm	10 ft.lb. 10 Nm	3/4"	26.5" 675mm	Plastic Blow Molded	7 lb 3.15 Kg	YES
D4-600F	0-600 ft.lb. 0-800 Nm	10 ft.lb. 10 Nm	3/4"	48" 1220mm	Plastic Blow Molded	7 lb 3.15 Kg	YES
D4-1000F	0-1000 ft.lb. 0-1400 Nm	20 ft.lb. 20 Nm	1"	77" with extension 1960mm	Metal	20 lb 9 Kg	YES
D4-2000F	0-2000 ft.lb. 0-2800 Nm	40 ft.lb. 50 Nm	1"	77" with extension 1960mm	Crdb	46 lb 21 Kg	YES