

POWER PACKS FOR HYDRAULIC TORQUE WRENCHES

Hydraulic Torque Wrench Pumps - Electric & Pneumatic

- ♦ Working pressure: 70 ~ 700 bar.
- The pressure can be adjusted precisely.
- 2-stage pump, quick retract and highly efficient.
- 2 to 8 Oil output, 1 to 4 hydraulic wrenches can work simultaneously.
- Oil tank volume: 3.7 to 9.5 Ltr. capacity.
- · Special twin hose with quick coupling.
- · Can be operated by remote control.
- · Cooling system inbuilt in specific models.
- · Power Pack can be available with higher flow rate.
- · Fan cooled heat exchanger optional can provide on request.







Part No.		TEP-109	TEP-111	TEP-114	TNP-111	TNP-114	TNP-81
Max. Pressure	Bar	700	700	700	700	700	700
Pump		2 Stage	2 Stage	2 Stage	2 Stage	2 Stage	2 Stage
Max. Flow	l/min.	10 Ltr.	11.8 Ltr.	11.8 Ltr.	11.1 Ltr.	11.1 Ltr.	8 Ltr.
Power Unit		230V50Hz	230V50Hz	230V50Hz	Air 80-100 Psi Vol. 50 CFM	Air 80-100 Psi Vol. 50 CFM	Air 80-100 Psi Vol. 50 CFM
Remote Cable	Mtr.	6	6	6	6	6	6
Tank Volumn	Ltr.	3.7	7.6	7.6	7.6	7.6	9.5
No. of tool work at a time		1	1	4	1	4	1
Approx. Size		500X225X350	435X240X460	435X240X460	420X240X500	420X240X500	420X240X500
Approx. Weight	Kg.	26	21	21.5	26	26.5	26