

HIGH PRESSURE HYDRAULIC HOSES


Hose End* Assemblies Couplers		Hose Length (m)	700-series Thermo Plastic		900-series Heavy Rubber	
End1	End2		Part No.	Weight(kg)	Part No.	Weight(kg)
1/4" NPTF	1/4" NPTF	1.8	-	-	GH-9206Q	1.2
	3/8" NPTF	1.8	-	-	GH-9206S	1.2
3/8" NPTF	3/8" NPTF	0.6	GH-7202	0.5	GH-9202	0.7
		0.9	GH-7203	0.7	GH-9203	0.9
		1.8	GH-7206	0.9	GH-9206	1.2
		3	GH-7210	1.4	GH-9210	1.8
		6	GH-7220	2.8	GH-9220	3.6
		9	GH-7230	4.5	GH-9230	5.9
		15	GH-7250	7.0	GH-9250	9.1



PRESSURE GAUGE ADAPTORS

- ◆ Pressure gauge adaptors (GA-series).
- ◆ Convenient for pressure gauge fitting to the system.
- ◆ Male end into pump or cylinder pot, female end accepts hose or coupler, 3rd port is for gauge connection.
- ◆ Above 700 bar swivel connection, please contact for details.

Part No.	Gauge Port NPTF	Male End NPTF	Female End NPTF
GA-1	1/4"	3/8"	3/8"
GA-2	1/2"	3/8"	



MANIFOLDS

Part No.	Products Description	
A-64	178mm Long Manifold with 7 female ports	
A-65	369mm Long Manifold that allows direct mounting of control valves to the manifold. Plugs 3/8" NPTF	
A-66	6-port Hexagon Manifold Plugs furnished for all ports 3/8" 18 NPTF	
AM-2	Permuted Manifold Functions as split-flow valve to control two single-acting cylinders simultaneously. All ports 3/8"-18 NPTF	
AM-4		

HIGH PRESSURE HYDRAULIC HOSES

Part No.	Hose Length (m)	Max. Pressure (bar)	Weight (Kg)
G206085	3	1000	1.5
G206086	6	1000	3.0
G206087	9	1000	4.8
G206088	3	1800	1.5
G206089	6	1800	3.0
G206089-1	9	1800	4.8
G206090	3	2620	1.5
G206091	6	2620	3.0
G206092	9	2620	4.8
G206093	3	3200	1.6
G206094	6	3200	3.3
G206095	9	3200	5.1



QUICK COUPLERS

- ◆ 3/8" high flow couplers, Max. Working pressure : 700 bar, these couplers are the standard parts of most hydraulic cylinders (jacks) and other tools.
- ◆ 1/4" ultra-pressure quick couplers, Max. working pressure : 1500 bar. It can be used for hydraulic torque wrench, we can choose the suitable model for customers' request.



Max. Working Pressure (bar)	Type of the Coupler	Complete Set Part No.	Coupler Female Part No.	Coupler Male Part No.	Outside Size (mm)
700	High Flow Coupler	C-604	CR-400	CH-604	3/8" NPT
700	High Flow Quick Coupler	CT901	C901	T901	1/4" NPT
1000	Ultra-Pressure Quick Coupler	CT115	C115	T115	G1/4
1500	Ultra-Pressure Quick Coupler	CT116	C116	T116	G1/4

PRESSURE GAUGES

- ◆ Dual scale reading in bar and psi, all pressure sensing parts sealed and dampened by glycerine for long life.
- ◆ Safe, simple, efficient and stainless steel structure can resist strong corrosion.



Pressure Range		Ø63 1/4 NPFT LOWER MOUNT (PART NO.)	Ø100 1/2 NPFT LOWER MOUNT (PART NO.)
(bar)	(psi)		
0-700	0-10000	701201	-
0-1000	0-15000	701202	-
0-1500	0-25000	-	701216
0-2500	0-40000	-	701217
0-3000	0-45000	-	701218